

NURSING HOME CHECKLIST

Physical Plant – New Construction

This checklist is a guide and not intended to be a substitute for MN Rules.

MN Rule Reference, Subp. (http://www.revisor.mn.gov/rules/4658/version/2014-01-18T06:53:54-06:00)

Requirement	MN Rule Reference, Subp.	ОК
ARCHITECTURAL		
Site Requirements (if new facility)	4658.4040	
Bedrooms:		
5% of total bedrooms a private remaining are double	4658.4100	
Above grade rooms; adjacent rooms do not share toilets (CMS)	4658.4105, 7	
Floor area 120 SF private, 100 SF/bed	4658.4105	
Bed clearances, doors 44" W	4658.4105/4110	
Dining/Dayroom/Activity: 40 SF/bed	4658.4200	
Windows: dayroom/dining	4658.4205/4210	
Nurse Station:		
140 ft from bedrooms	4658.4105, 8	
Provides supervision of corridors	4658.4125, 2	
Nurses' toilet nearby	4658.4125, 3	
Hand washing lav. In station	4658.4125, 2	
Clean Utility (CU):		
Cabinets, shelves	4658.4125, 4	
Sink w/institutional fittings, towel disp.	4658.4125, 4	
Medicine Room:		
(same as CU + refrigerator)	4658.4125, 2	
Double lock for narcotics	4658.1340, 1	
Soiled Utility:		
In residential wings	(recommended)	
Clinical sink, sink w/ institutional fittings	4658.4125, 5	
Cabinets & shelves, towel disp.	4658.4125, 5	
Bedpan washer/sanitizer	4658.4125, 5	
Corridors:		
8 ft. wide	4658.4120, 2	
Handrails each side:		
1½" to 2" diameter, 32-34" to top of rail, 1½" clear to wall	4658.4120, 2	
Bedroom Windows:		
30"H sills	4658.4105, 6	
Clear space 30 ft. @ 65 deg. angle	4658.4105, 6	
Window area is 1/8 bedroom area	4658.4105, 6	
Central Bathing:		
1 tub & 1 shower min; 1 per 20 beds	4658.4135	
Direct access to WC and lavatory	4658.4155, 2D	

Requirement	MN Rule Reference, Subp.	ОК
Clearances	4658.4155, 4A	
If shower, splash wall	4658.4155, 3A	
Toilet Rooms:		
Direct access from only one bedroom (CMS)	4658.4140	
Doors 32" clear & swinging out	4658.4145, A	
WC and lavatory in room, mounting	4658.4135	
3 ft. 6" min width, clearances	4658.4145, B	
Private for single bedrooms	4658.4100	
Special toilet rooms 6x5½ ft. (4 ft. clear in front of toilet)	4658.4150, C	
Toilet paper holder	4658.4145, E/4150, F	
Storage Space: 15 SF per bed	4658.4710	
Janitor's Closet: (floor sink, shelves)	4658.4175	
Entrance: canopy to curb (HC access)	4658.4360	
Public Toilets/Lobby: near main entry	4658.4135	
PT Area (if provided):		
Special toilet room in area	4658.4370	
Cubicle curtains	4658.4370	
Supervisor space, storage space	4658.4370	
Lavatory/sink w/ institutional fittings, towel dispenser	4658.4370	
Activity Area:		
Toilet room nearby	(recommended)	
HC accessible sink, counter	4658.4215	
Storage space, display space	4658.4215	
Barber/Beauty Shop:		
Storage space	4658.4375	
Shampoo sink	4658.4375	
Kitchen:		
Dishes flow	4658.4300, 1	
Food storage (delivery access)	4658.4300, 1	
Sep. Jan. closet & toilet room	4658.4300, 5 & 7	
Cart washing	4658.4315	
Can washing area (outside kitchen)	4658.4320	
Partition (dishwashing area)	4658.4310, B	
4 ft. aisles throughout	4658.4305, 1	
Lavatories (food prep./dishwashing)	4658.4300, 6	
Enclosed storage for dishes, utensils, pots pans	4658.4300, 4	
Laundry Room /Area:		
Work flow	4658.4335	
Cart storage	4658.4335	
Soiled linen room	4658.4330	
Laundry processing room (washers, dryers, 2-comp. sink, lav., tbls.)	4658.4335	
Clean linen room (separate & enclosed)	4658.4345	
Nourishment Area:		
Counter & sink	4658.4130	\bot
Cabinets, refrigerator		

Requirement	MN Rule Reference, Subp.	ОК
Ref. Drinking Fountains: For resident areas, activities, dining	4658.4160	
Elevator:		
5 ft. W x 7 ft. D	4658.4415	
Door opening 44" wide	4658.4415	
Ceiling Heights:		
8 ft. living areas	4658.4455	
7 ft. 6 in. corridors, other rooms	4658.4455	
9 ft. min. boiler rooms	4658.4455	
Lever Type Door Handles	4658.4405	
Cubical curtains:		
2-bed rooms	4658.4105, 1	
Central bathing	4658.4155, 2A	
PT	4658.4370, 1	
Grab Bars:		
Showers and tubs	4658.4155, 3C & 4D	
All toilets, grab bars 10" above seat (except staff)	4658.4145, F/4150, G & H	
Plumbing Fixture Maintaining:		
Lavatories	4658.4145, H/4150, J	
Water closets	4658.4145, B & C/4150, C & D	
Sterilizer (if provided): in CU room	4658.1900	
MECHANICAL		
Heating System:		
Maintain 71-81° F	4658.4510, 1	
Indirect fired (including range make up air)	4658.4550, 1	
Humidity: Maintain 25-50%	4658.4510, 1	
Hot Water:		
105-115° F with recirculation180/160° F at dish/clothes washers	4658.4510, 1	
Dishwasher:		
Pressure gauge	4658.4500, 5	
Pressure reducing valve, vacuum breaker	4658.4500, 5	
Floor drain w/o backwater valve	4658.4500, 5	
Food Storage Areas: no floor drains	4658.4500, 6	
Bedpan Cleaning Device: (SU sinks)	4658.4505, 2	
Washer/Sanitizer: indirect waste	MN Plumbing Code	
Sterilizer:		
Indirect waste	4658.4505, 3	
Independently vented	4658.4505, 3	
Valves/Controls: easy access	4658.4510, 3	
Ventilation:	1000.1010,0	
Meets table	4658.4520	
Exhaust to outside from all ranges	4658.4520	
Air Conditioning: after 6/30/88	Statute 144A, 1b	
Humidification: effective Nov 1996	Statute 1447, 10	
Relative humidity 25% min to 50% max	4658.4510, 1	

Requirement	MN Rule Reference, Subp.	ОК
Fresh Air Intake:	4658.4525	
25 ft. from exhaust, parking height above grade or above roof		
Exhaust or Waste Chute Vent: 25 ft. from openable windows	4658.4525	
Filtered Outside Air: 25% efficient	4658.4550, 2 & 3	
Filtered Kitchen Exhaust Hoods	4658.4535, 1	
Institutional Fittings: (lavatories, sinks)	4658.4505, 1	
Radiation Elements: 4" above floor	4658.4510, 4	
Air registers: 4" above floor	4658.4530	
Medical Gas System (if any)	(certification)	
ELECTRICAL		
Light/Power Panels: typed index	4658.4600, 1	
Corridor Receptacles: 50 ft. spacing	4658.4605	
Four-plex Receptacles: on headwall on each side of each bed	4658.4625	
Night Light: each bedroom	4658.4630	
Nurse Call System:	4658.4635	
Registers at central annunciator	4658.4635	
Registers at bedroom door	4658.4635	
Duty signal @ Med. Rm., CU/SU Rms., and Nourishment Stations	4658.4635	
Emergency calls at resident toilets and bathing fixtures, and in dayrooms, therapy and activity areas	4658.4635	
Nurse call device @ each bed	4658.4635	
Zone lights where required	4658.4635	
Door Alarms:		
At exits	4658.0065	
Emergency generator (+ light)	4658.0065	
Keyed Power Switch: with indicator light at the electric range	4658.4130	
No lamps exposed to incidental damage	(safety)	